

JURNAL

**THE EFFECT OF REINFORCING STEEL CORROSION ON THE ADHESIVE
STRENGTH OF REINFORCED CONCRETE (CASE STUDY OF THE FACULTY
OF VETERINARY MEDICINE BUILDING MUHAMMADIYAH UNIVERSITY OF
WEST SUMATERA)**

Diajukan Sebagai Salah Satu Syarat Untuk Memperoleh Gelar Sarjana Teknik
Pada Program Studi Teknik Sipil Fakultas Teknik
Universitas Muhammadiyah Sumatera Barat



OLEH :

ATTASHWIRUL FANNI

20180003

PROGRAM STUDI TEKNIK SIPIL

FAKULTAS TEKNIK

UNIVERSITAS MUHAMMADIYAH SUMATERA BARAT

2024

HALAMAN PENGESAHAN JURNAL


THE EFFECT OF REINFORCING STEEL CORROSION ON THE
ADHESIVE STRENGTH OF REINFORCED CONCRETE (CASE STUDY
OF THE FACULTY OF VETERINARY MEDICINE BUILDING
MUHAMMADIYAH UNIVERSITY OF WEST SUMATERA)

Oleh :

ATTASHWIRUL FANNI

20180003


Dosen Pembimbing I



Ir. Deddy Kurniawan, S.T., M.T

NIDN.1022018303

Dosen Pembimbing II



Asiya Nurhasanah Habirun, S.ST., M.Eng

NIDN. 1022119101

Dekan Fakultas Teknik

UM Sumatera Barat,




Dr. Eng. Ir. Masril, S.T., M.T

NIDN.1005057407

Ketua Program Studi

Teknik Sipil



Helga Yermadona, S.Pd, M.T

NIDN.1013098502

LEMBAR PERSETUJUAN TIM PENGUJI

Jurnal ini telah dipertahankan dan disempurnakan berdasarkan masukan dan koreksi Tim Penguji pada ujian tertutup pada tanggal 20 Agustus 2024 di Fakultas Teknik Universitas Muhammadiyah Sumatera Barat.

Bukittinggi, 20 Agustus 2024

Mahasiswa



Attashwirul Fanni

NIM.20180003

Disetujui Tim Penguji Jurnal Tanggal 20 Agustus 2024 :

1. Ir. Deddy Kurmiawan, S.T., M.T

1. 

2. Asiya Nurhasanah Habirun, S.ST., M.Eng

2. 

3. Ir. Zubeldi, S.T., M.T

3. 

4. Helga Yermadona, S.Pd, M.T

4. 

Mengetahui

Ketua Program Studi

Teknik Sipil



Helga Yermadona, S.Pd, M.T

NIDN. 1013098502

LEMBAR PERNYATAAN KEASLIAN

Saya yang bertanda tangan dibawah ini :

Nama Mahasiswa : Attashwirul Fanni
Tempat Tanggal Lahir : Bukittinggi, 25 September 2002
NIM : 20180003
Judul Jurnal : The Effect Of Reinforcing Steel Corrosion On The Adhesive Strength Of Reinforced Concrete (Case Study Of The Faculty Of Veterinary Medicine Building Muhammadiyah University Of West Sumatera)

Menyatakan dengan sebenarnya bahwa penulisan Jurnal ini berdasarkan hasil penelitian, pemikiran dan pemaparan asli dari saya sendiri, baik untuk naskah laporan maupun kegiatan yang tercantum sebagai bagian Jurnal ini. Jika terdapat karya orang lain, saya akan mencantumkan sumber yang jelas.

Demikian pernyataan ini saya buat dengan sesungguhnya dan apabila dikemudian hari terdapat penyimpangan dan ketidakbenaran dalam pernyataan ini, maka saya bersedia menerima sanksi akademik berupa pencabutan gelar yang telah diperoleh karena karya tulis ini dan sanksi lain sesuai dengan peraturan yang berlaku di Universitas Muhammadiyah Sumatera Barat.

Demikian pernyataan ini saya buat dalam keadaan sadar tanpa paksaan pihak manapun.

Bukittinggi, Agustus 2024

Yang membuat pernyataan,



Attashwirul Fanni

NIM. 20180003

THE EFFECT OF REINFORCING STEEL CORROSION ON THE ADHESIVE STRENGTH OF REINFORCED CONCRETE (CASE STUDY OF THE FACULTY OF VETERINARY MEDICINE BUILDING, MUHAMMADIYAH UNIVERSITY OF WEST SUMATRA)

¹ATTASHWIRUL FANNI,²DEDDY KURNIAWAN,³ASIYA NURHASANAH HABIRUN

^{1,2,3} Department of Civil Engineering, Faculty of Engineering, Muhammadiyah University of Sumatera Barat, Bukittinggi, Indonesia

Author's email:

¹attashwirulf@gmail.com;²deddydk22@gmail.com;³asiya2021ce@gmail.com

¹attashwirulf@gmail.com

Abstract. *The construction of the UM West Sumatra Faculty of Veterinary Medicine Building has been stopped until the work on the columns has left 1.5 meters of overstep reinforcement on each column since 2021. During this period, the rebar experiences uniform corrosion along the rebar which causes a reduction in the cross-sectional area of the steel reinforcement so that the bearing capacity of the steel will decrease. This study compared the strength of concrete bonding with corrosion and non-corrosion reinforcement bars before construction resumed. The method carried out is a cube bond test with reinforcing steel embedded into concrete as deep as the height of the mold, and the test is done using a compression testing machine (CTM). K-250 concrete specimens of 15X15X15 size equipped with corrosion and non-corrosion D19 reinforcement were made for bonding strength test at 28 days of age. The results showed that the bonding strength of concrete with corrosion reinforcing steel was quite low, which was 0.60 N/mm², and the bonding strength of concrete with non-corrosion reinforcing steel was higher, which was 1.68 N/mm². Based on the results of this study, it is better that before the construction work continues, corrosion on all rebar surfaces must be cleaned first.*

Keywords: *Bond Strength; Corrosion; Reinforced Concrete*

1. INTRODUCTION

Concrete is a construction material that has a high compressive strength value and is weak in resisting tensile force. A combination of concrete and reinforcing steel is required to bear the tensile force arising from the working load. Reinforced concrete can work in bearing loads due to the strong adhesion factor between the concrete and the reinforcing surface. One of the causes of the weak adhesion system between concrete and rebar is corrosion. Corrosion on steel rebar in addition to causing a reduction in surface area also causes a volume of compounds resulting from corrosion reactions that is greater than the volume of reacting steel. This can cause the concrete covers to crack if this damage continues, then the concrete building is no longer suitable for use (Rasyid et al., 2021).

There are many construction projects whose work has stopped due to various things and on average the project has stopped working on columns made of reinforced concrete. The work on abandoned structures often allows reinforcing steel to be exposed to natural conditions continuously for a long time. Reinforcement steel that is exposed to natural conditions will undergo corrosion and if the reinforcement is cast immediately, it will have a bad impact on the performance of reinforced concrete, especially the performance of strong adhesion.

Based on previous research conducted by Arief Subakti Ariyanto, the impact of corroded reinforcing steel on construction is not only strong adhesion that is affected, the occurrence of corrosion in a building can affect the service life of the building, because the performance of building structural components decreases. To achieve the life of the building according to the plan, continuous maintenance of the building and maintenance of the building is required (Ariyanto, 2022).

The construction of the Faculty of Veterinary Medicine Building, Campus IV, University of Muhammadiyah West Sumatra is one example of a development project that has been stopped since 2021 so that the construction project leaves 1.5 meters of

reinforcement in each column. The development project is a case study in this study that will outline how the effect of corrosion on reinforcing steel on the adhesion strength of reinforced concrete considering that reinforced concrete is the most important part of the building structure. This study will also compare the adhesion strength between reinforced concrete using corroded reinforcement steel and non-corroded reinforced concrete.

2. LITERATURE REVIEW

2.1 Reinforced Concrete Forming Materials

According to SNI 2847:2013 concrete is a mixture of Portland cement or other hydraulic cement, fine aggregate, coarse aggregate, and water, with or without additives that form a solid mass. According to SNI 03-2847-2002, lightweight concrete is concrete that contains lightweight aggregate and has a specific gravity of not more than 1900 kg/m³.

1. Cement

According to SNI 03-2847-2002 (Procedures for Calculating Concrete Structures for Buildings) several types of cement must meet several conditions to be able to become a concrete forming material.

- SNI 15-2049-1994, Portland cement.
- "Specification of hydrolyzed blended cement" (ASTM C 595), except for types S and SA which are not intended as the main binding elements of concrete structures.
- "Specification of expansive hydraulic cement" (ASTM C 845).

2. Aggregate

Aggregate is a granular material, such as sand, gravel, crushed stone, and incandescent furnace crust that is used together with a binding medium to build a concrete or hydraulic cement mixture (SNI - 03 - 2847 - 2002, n.d.). Aggregate for concrete must meet one of the following conditions:

- "Aggregate specifications for concrete" (ASTM C 33).
- SNI 03-2461-1991, Specification of lightweight aggregate for structural concrete.

The maximum nominal size of the coarse aggregate must not exceed:

1. 1/5 of the smallest distance between the sides of the mold,
2. 1/3 of the thickness of the floor slab,
3. 3/4 minimum net distance between rebar–reinforcement or wire–wire, rebar bundles, or prestressed tendons or sleeves

3. Water

The water used in the concrete mixture must be clean and free of damaging materials containing oils, acids, alkalis, organic matter, or other materials that are detrimental to concrete or reinforcement. Mixing water used in prestressed concrete or on concrete embedded with aluminum metal, including free water contained in aggregates, must not contain harmful amounts of chloride ion (SNI - 03 - 2847 - 2002, n.d.). According to ASTM C 109, non-potable water should not be used as a concrete mixing agent unless it meets the following conditions:

- The selection of the proportion of concrete mixture should be based on the concrete mixture that uses water from the same source.
- The results of the 7- and 28-day age tests on mortar test cubes made from a water mixture are not potable and must have a strength equal to at least 90% of the strength of the test piece. The comparison of such strength tests shall be carried out on similar mixtures except on the mixing water made and tested following the "Compressive strength test method for hydraulic cement mortars".

4. Reinforcing steel

Based on SNI 03-2847-2002 (Procedures for Calculating Concrete Structures for Building Buildings), rebar is a plain or threaded or pipe-shaped steel bar that functions to withstand tensile force on concrete structural components, excluding prestressed tendons, unless specifically included. Threaded rebar steel (BJTD) must meet one of the following conditions :

- "Specification for threaded and plain billet steel bars for concrete reclamation" (ASTM A 615M).
- "Specifications for threaded and plain axle steel bars for concrete reclamation" (ASTM A 617M).
- "Specifications for low alloy threaded and plain steel for concrete reclamation" (ASTM A 706M).

2.2 Compressive Strength of Concrete

According to SNI 03-1974-1990, the compressive strength of concrete is the magnitude of the load per unit area, which causes the concrete test piece to be destroyed when loaded with a certain compressive force, which is generated by the pressing machine. The compressive strength of concrete identifies the quality of a structure, where the higher the level of structural strength desired, the higher the quality of the concrete produced (PB.1989:16). The compressive strength of concrete will increase with the increase in the age of concrete. In certain cases, the compressive strength of concrete will continue to increase until a few years later. Usually, the compressive strength of concrete plans is calculated at the age of 28 days. The rate of increase in the age of concrete is highly dependent on the use of cement because cement tends to directly improve its pressing performance. Compressive strength is calculated by equation 2.1.

$$f_c' = \frac{P}{A} \quad (2.1)$$

Description :

f_c' = Compressive Strength of Concrete (MPa)
P = Maximum load (N)
A = Cross-sectional area of the test piece (mm²)

2.3 Strong Adhesion of Reinforced Concrete

In general, the use of steel reinforcement in reinforced concrete structures is to replace the ability to receive tensile force on weak concrete materials. The tensile force that occurs in the concrete structure will then be channeled to the steel reinforcement through an adhesion mechanism (bond), so that the two materials, namely concrete and steel reinforcement, can work together into a single composite material (Ngudiyono et al., 2022). The adhesion mechanism between concrete and reinforcing steel will form a composite action in bearing the load. The adhesion between concrete and rebar steel is influenced by several factors, one of which is the compressive strength of concrete. The adhesion between concrete and threaded reinforcing steel is formed by adhesion, friction, and mechanical interlocking. Mechanical interlocking makes a great contribution to forming an adhesion between concrete and steel. Based on this mechanism, the transfer of force from rebar steel to concrete occurs through the stranding of reinforcing steel (Purwanto et al., 2023).

The adhesion mechanism between concrete and reinforcing steel will form a composite action in bearing the load. The adhesion between concrete and rebar steel is influenced by several factors, one of which is the compressive strength of concrete. The adhesion between concrete and threaded reinforcing steel is formed by adhesion, friction, and mechanical interlocking. Mechanical interlocking makes a great contribution to forming an adhesion between concrete and steel. Based on this mechanism, the transfer of force from rebar steel to concrete occurs through the stranding of reinforcing steel (Purwanto et al., 2023). The adhesion strength of reinforced concrete can be calculated by the following equation 2.2.

$$u = \frac{P_{max}}{\pi \cdot d \cdot l} \quad (2.2)$$

Description :

u = Adhesion strength of reinforcement (MPa)
d = Rebar diameter (mm)
P_{max} = Maximum tensile load (N)
L = Length of embedded reinforcement (mm)

2.4 Effect of Corrosion on Reinforced Concrete

Corrosion is the process of oxidation of a metal with air or other electrolytes, where air or electrolyte will undergo reduction, so the corrosion process is an electrochemical process. Corrosion occurs through redox reactions, where metals undergo oxidation, while oxygen undergoes reduction. Rust on iron is a brown-red substance (Ariyanto, 2022). Factors that can accelerate the occurrence of corrosion are water and electrolytes (acids or salts). If the reinforcing steel is left in the open for a long time, the reinforcing steel will be in direct contact with rainwater and will accelerate the corrosion process.

One of the main problems in construction work is corrosion in reinforcing steel. Many construction projects continue to use rebar even though they have been corroded. Corrosion on reinforcing steel will cause a decrease in the cross-sectional area so that the adhesion strength between rebar and concrete will be reduced so that the reinforced concrete structure will experience a decrease in structural strength and concrete will peel off and even collapse.

3. RESEARCH METHODS

The research method in this study is an experiment conducted at the Engineering Laboratory of the University of Muhammadiyah West Sumatra.

3.1 Sample Preparation

There are 2 types of reinforcing steel used, namely deformed D19 non-corroded bar purchased at the nearest building store, deformed D19 bar that has corroded, and sampling at the construction project of the Faculty of Veterinary Medicine Campus IV of the University of Muhammadiyah West Sumatra. The length of the rebar steel used is \pm 20 cm each placed in the middle of the cube mold with an embedment length of 15 cm.

3.2 Material Preparation

The quality of concrete planned for concrete compressive strength and bond test is K250 concrete quality. Before making a sample, the material to be used is tested first. Material property tests are carried out on fine aggregate materials, coarse aggregates, and cement. In testing material properties, there are several types of tests, namely:

- a. Cement
 - Specific gravity of cement
- b. Fine aggregate
 - Specific gravity of fine aggregate
 - Fine aggregate volume weight
 - Fine aggregate fineness modulus
 - Test of material passing sieve no.200
 - Fine aggregate organic matter examination
 - Fine aggregate sludge level inspection
 - Fine aggregate moisture content testing
 - Specific gravity
- c. Coarse aggregate
 - Coarse aggregate specific gravity
 - Gross aggregate volume weight
 - Coarse aggregate fineness modulus
 - Examination of coarse aggregate organic substances
 - Coarse aggregate sludge content inspection
 - Crude aggregate moisture content testing
 - Specific gravity

3.3 Mix Design

In general, the volume contained in concrete is \pm 68% aggregate, \pm 11% cement, \pm 17% water, and \pm 4% air. Because of the cement hydration process that occurs, water and cement can attach aggregate granules until a solid mass such as stone is formed (Safitri, 2021).

3.4 Sample Testing

After obtaining the results of the mix design, the data from the mix design is used as a benchmark to make a concrete mixture which is then carried out a slump test with the provision of reducing the concrete mix ± 10 cm. After getting the results of concrete mixing according to the plan, fresh concrete is molded into a cube-shaped mold with a size of 15x15x15 cm. The molded concrete is removed from the mold after reaching a 24-hour lifespan. Furthermore, the concrete is cured by soaking the concrete in a water bath for 25 days and is removed for air drying for 3 days.

Concrete compressive strength testing is carried out according to SNI 1974:2011 procedures using the Compression Testing Machine (CTM) compressive strength testing equipment. Concrete that is 28 days old is tested by applying a maximum load characterized by cracks or collapse in the test piece.

The bond test specimen is in the form of a cube with a size of 15x15x15 cm and reinforcing steel is embedded into concrete as deep as the height of the mold, which is 15 cm with the quality of the concrete plan K250. Bond test testing is also carried out using a Compression Testing Machine (CTM) by way test pieces that have reached the age of 28 days are inserted into the CTM device. On the surface of the base of the test piece, a base that has been perforated in the center with a hole diameter of ± 23 mm and a depth of 5 cm. The empty cavity created by the perforated base allows the reinforcement to slide into it without any hindrance when it is forced or axially pressed from above. The concrete sample is then pressed with a maximum load until the test specimen undergoes adhesion collapse (bond stress failure) so that the magnitude of the compressive force will be obtained. The results of these tests are then analyzed and used to make data-driven decisions.

4. RESULTS AND DISCUSSION

4.1 Mechanical Properties of Concrete

In this research, the materials used are coarse aggregate derived from Palembang crushed stone, fine aggregate from Palembang tidal sand, and Portland Composite Cement (PCC) type of Padang cement. The results of the material test are presented in Table 1.

Table 1. Mechanical Properties of Concrete K250

| Material | Testing | Result | SNI | |
|------------------|------------------------------------|--------|------------|---|
| Cement | Specific Gravity | 2,83 | 3 – 3,20 | x |
| Fine Aggregate | Specific Gravity | 2,51 | 2,5 – 2,7 | ✓ |
| | Aggregate Volume Weight (%) | 1,37 | 1,4 – 1,9 | x |
| | Modulus of Fineness (%) | 3,26 | 1,5 – 3,8 | ✓ |
| | Filter Passing Material No.200 (%) | 3,08 | ≥ 5 % | ✓ |
| | Sludge Content (%) | 4,95 | ≥ 5 % | ✓ |
| Coarse Aggregate | Specific Gravity (%) | 2,59 | 2,4 – 2,8 | ✓ |
| | Aggregate Volume Weight (%) | 1,61 | 1,4 – 1,9 | ✓ |
| | Modulus of Fineness (%) | 4,55 | 6 – 7,1 | x |
| | Moisture Content (%) | 1,24 | 0,5 - 5 | ✓ |

Source: Personal data, 2024

4.2 Mix Design

In this study, the mix design was carried out by SNI 03-2834-2000 (Procedures for Making Normal Concrete Mixed Plans) with the quality of the K250 or f_c' plan concrete 20.75 MPa. The mix design for 1 test piece is obtained from the results of testing the concrete-forming properties described in Table 2.

Table 2. Mix Design Concrete K250

| | | |
|------------------|-------|----|
| Cement | 1,263 | Kg |
| Water | 0,682 | Kg |
| Coarse Aggregate | 1,857 | Kg |
| Fine Aggregate | 3,151 | kg |

Source: Personal data, 2024

4.3 Concrete Compressive Strength Testing

Compressive strength testing is carried out using a CTM (compression testing machine) tool. The compressive strength test was carried out after the concrete reached the age of 28 days and had been cured for 25 days by soaking the concrete in a water bath and removing it for air drying for 3 days.

Table 3. Results of Concrete Compressive Strength Test K250

| No | Weight (kg) | Area mm ² (A) | Load (KN) | Load (N) | Compressive Strength (Mpa) | Kg/cm ² | SD | Σ | fc' (Mpa) | Specifications | SNI |
|----|-------------|--------------------------|-----------|----------------|----------------------------|---------------------|-------|---------------|-----------------|----------------|-----|
| a | b | c | d | e = (d) x 1000 | f = (d) / (c) x 10 | g = (g) x 0.83 x 10 | h | i = (g) + (h) | j = (i) x 0.083 | | |
| 1 | 7,082 | 225000 | 430 | 430000 | 19,11 | 230,25 | 9,117 | 239,37 | 19,868 | | x |
| 2 | 7,113 | 225000 | 435 | 435000 | 19,33 | 232,93 | 9,117 | 242,05 | 20,790 | | ✓ |
| 3 | 7,540 | 225000 | 460 | 460000 | 20,44 | 246,32 | 9,117 | 255,44 | 21,201 | | ✓ |
| 4 | 7,467 | 225000 | 470 | 470000 | 20,89 | 251,67 | 9,117 | 260,79 | 21,646 | | ✓ |
| 5 | 7,582 | 225000 | 465 | 465000 | 20,67 | 249,00 | 9,117 | 258,11 | 21,423 | | ✓ |

Average compressive strength = 20,85 MPa

Source: Personal data, 2024

Based on Table 3, the compressive strength applied to 5 samples produced an average compressive strength of fc' 20.85 MPa. The result meets the quality of the planned concrete, which is fc' 20.75 MPa.

4.4 Bond Test

Based on ASTM C.234 – 1980 (Standard Test Method for Comparing Concretes based on the Bond Developed with Reinforcing Steel) bond test is carried out to calculate the amount of shear force between reinforcement and concrete through a compression test. Threaded reinforcing steel is designed to be strong in concrete adhesion and high rebar, reinforcing steel is used to withstand the compressive force of concrete along with tensile reinforcing steel.

To calculate the adhesion strength between concrete and reinforcement or the shear force against the reinforcement can be calculated by equation 4.1.

$$\tau = \frac{P_{max}}{\pi D t} \quad (4.1)$$

Description:

P max = Maximum press load (KN)

D = Diameter of reinforcing steel (mm)

t = Height of reinforced steel covered in concrete (mm)

π = 22/7

Table 4. Testing of Corroded Deformed Bar D19 Adhesion Strength

| Concrete Age | | 28 days | | |
|---|-------------------|---------|------|------|
| Sample | | I | II | III |
| Maximum Compressive Strength | KN | 5 | 7 | 4 |
| Reinforcement Diameter | mm | 19 | 19 | 19 |
| Length of Reinforcement Covered in Concrete | mm | 150 | 150 | 150 |
| Strong Adhesion | N/mm ² | 0,56 | 0,78 | 0,45 |
| Average Strong Adhesion | N/mm ² | 0,60 | | |

Source: Personal data, 2024

Based on Table 4, the results of the reinforced concrete bond test using D19 deformed bars have very low corrosion, namely 0.60 N/mm². This is because corrosive substances erode the surface layer of rebar steel and result in a reduction in the bearing capacity of rebar steel in resisting the tensile force and bonding between rebar steel and concrete.

Table 5. Testing of Deformed Bar D19 Non-Corrosion Adhesion Strength

| Concrete Age | | 28 days | | |
|---|-------------------|---------|------|------|
| Sample | | I | II | III |
| Maximum Compressive Strength | KN | 20 | 15 | 10 |
| Reinforcement Diameter | mm | 19 | 19 | 19 |
| Length of Reinforcement Covered in Concrete | mm | 150 | 150 | 150 |
| Strong Adhesion | N/mm ² | 2,24 | 1,68 | 1,12 |
| Average Strong Adhesion | N/mm ² | 1,68 | | |

Source: Personal data, 2024

Based on Table 5, the results were obtained that the bond test of reinforced concrete using non-corroded D19 deformed bars was higher than that of reinforced concrete using corroded deformed bars, which was 1.68 N/mm². Based on the comparison of the results of the bond test between corroded D19 deformed bar and non-corrosive D19 deformed bar, it can be concluded that before reinforcing steel is used to make reinforced concrete, it is better to ensure that there are no corroded parts by cleaning the corroded reinforcing steel surface.

CONCLUSION

The conclusions obtained from this study are:

1. The compressive strength value of normal concrete is 20.85 MPa
2. The adhesion strength value of reinforced concrete using BJTD 19 which is not corrosive is higher, which was 1.68 N/mm², compared to reinforced concrete using BJTD 19 corrosion, which was 0.60 N/mm².
3. Corrosion in rebar steel can cause the diameter of the rebar cross-section to decrease because the corrosive substance erodes the rebar layer. Because of this, the carrying capacity of reinforced concrete is reduced in bearing the load.
4. The bonding strength of reinforced concrete with a corrosion-reinforcing bar is low because the concrete reacts with corrosive substances.
5. Before continuing the work on the structure, the corroded reinforcing steel should be cleaned first.

REFERENCES

1. ASTM C.234 - 1980: Standard Test Method for Comparing Concretes on the Basis of the Bond Developed with Reinforcing Steel. American Standard Testing and Material (ASTM Internasional).

- Ariyanto, A. S. (2022). Korosi pada Baja Tulangan dan Pencegahannya (Studi Kasus Gedung Ruko Yos Sudarso Square Semarang). *Jurnal Pendidikan Tambusai*, 6(1), 3036–3041.
- Ngudiyono, N., Merdana, I. N., Mahmud, F., Kencanawati, N. N., & Eniarti, M. (2022). PENGARUH TEMPERATUR TINGGI TERHADAP KUAT LEKAT DAN INITIAL CORROSION TULANGAN BAJA DALAM BETON. *Konstruksia*, 13(2), 33.
<https://doi.org/10.24853/jk.13.2.33-41>
- Purwanto, E., Basuki, A., Yani, M., & Yusuf, A. (2023). PENGARUH SIRIP VERTIKAL PADA KUAT LEKAT PELAT SETRIP DENGAN BETON NORMAL. November, 16–17.
- Rasyid, R., Sultan, M. A., Tata, A., & Setiawan, E. (2021). Efek Korosi Tulangan Terhadap Kapasitas Lentur Balok Beton Bertulang. *Clapeyron : Jurnal Ilmiah Teknik Sipil*, 3(1), 1–7.
<https://doi.org/10.33387/clapeyron.v3i1.4643>
- Safitri, D. (2021). Mix Design dan Pelaksanaan Campuran Beton. *Ilmuteknik.Org*, 1(3), 2021.
- SNI - 03 - 2847 - 2002. (n.d.). Tata Cara Perhitungan Struktur Beton Untuk Bangunan Gedung. SNI 03-2847-2002. STANDAR NASIONAL INDONESIA, 251.
- SNI (2013). SNI 2847:2013 : Persyaratan beton struktural untuk bangunan gedung. Badan Standarisasi Indonesia, Jakarta.
- SNI (2002). SNI 03-2847-2002: Tata Cara Perhitungan Struktur Beton Untuk Bangunan Gedung
- SNI (1990). SNI 03-1974-1990 : Metode Pengujian Kuat Tekan Beton. Badan Standardisasi Nasional.



International Conference on Innovations in Social Sciences Education and Engineering (ICoISSEE-4)

Bandung, Indonesia, July 20th, 2024

Bandung, June 12th, 2024

LETTER OF ACCEPTANCE

Dear **Attashwirul Fanni, Deddy Kurniawan and Asiya Nurhasanah Habirun**

We are pleased to inform you that your abstract titled **“The Effect of Reinforcing Steel Corrosion on the Adhesive Strength of Reinforced Concrete (Case Study of the Faculty of Veterinary Medicine Building, Muhammadiyah University of West Sumatra)”** has been accepted for the presentation in the **“International Conference on Innovations in Social Sciences Education and Engineering” (ICoISSEE-4), 2024**, organized by **LOUPIAS EVENT ORGANIZER JEJARING ILMU**, to be held on 20th July 2024 in Bandung, Indonesia. The conference is being organized in online mode.

The paper code assigned for your abstract is **032-ENG**. We request you to use this code for any further communication regarding your paper. We hope that you will register a maximum of one week from the issuance of this LoA. If you have already registered, please ignore this notification.

You are expected to send a complete paper to the **ICoISSEE-4** committee no later than **10th July 2024**. The presentation slide material is expected to be received by the committee no later than **15th July 2024**.

If you require further information, please do not hesitate to contact us.

Thank you for participating in the **ICoISSEE-4** conference. We are looking forward to seeing you at the conference.

Sincerely yours,
Chair of ICoISSEE-4



Henry Loupias

ICoISSEE-4

Bandung, Indonesia, 20th July 2024

Organized by



Co-Host



CERTIFICATE

This is to certify

Attashwirul Fanni

As Presenter



Presented a paper titled:

"The Effect of Reinforcing Steel Corrosion on The Adhesive Strength of Reinforced Concrete (Case Study Of The Faculty of Veterinary Medicine Building, Muhammadiyah University of West Sumatra)"

**The Fourth International Conference on Innovations in Social Sciences
Education and Engineering (ICoISSEE-4)**

Bandung, Indonesia, July 20th 2024

Supported by



Chair of Conference

A handwritten signature in black ink is written over a green rounded rectangular logo containing the text 'ICoISSEE-4' in white.

Henry Loupias